
tuulbachs

Dave Smith

Aug 23, 2020

CONTENTS:

1	Key Features	3
2	Quickstart	5
2.1	tuulbash	5
2.2	tuulcli	5
2.3	tuuldevops	5
2.4	tuulgit	6
2.5	tuulver	6
2.6	tuulyaml	7
2.7	install	7
2.8	deploy	7
2.9	internal API	8
2.10	Indices and tables	8
	Python Module Index	9
	Index	11

Automate low-level, repetitive, yet important development tasks related to semantic versioning, distributed version control, configuration parsing, and build pipelines.

**CHAPTER
ONE**

KEY FEATURES

- Increment semantic version parts for a versioned entity
- Manage the status of a local Git working tree
- Manage Git tags, local and remote, signed and unsigned
- Parse and update basic YAML configuration files

QUICKSTART

TBD

2.1 tuulbash

kickpy - A bash script intended to kick a Python script from an environment that doesn't have an established Python environment yet. For example:

```
./kickpy.sh example.py
```

2.2 tuulcli

Tuuls for command line interface (CLI).

Define colors and font styles for use in CLI output

```
class tuulcli.cli_color.CliColor
    Contain the list of colors and font styles
```

2.3 tuuldevops

Automation tuuls for common tasks around software development

Provide routines for outputting automated pipeline steps consistently

```
tuuldevops.pipeline_steps.major_step(title, description)
    Output title and description of a major step in the pipeline
```

Git tag the commit on the current branch with the current version of this software

```
tuuldevops.tag_current_version.tag_product_version(conf_filename)
    Git tag the commit on the current branch with the version of this software given in conf_filename
```

Update the version in the tuulbachs-formatted YAML version file

```
tuuldevops.update_version.update_product_version(conf_filename, new_ver)
    Write a new_ver as the new value for the 'version' key in the conf_filename
```

2.4 tuulgit

An opinionated set of Git tuuls.

Check the status of the local git working tree

`tuulgit.check_status.has_staged_uncommitted()`

Return a boolean indicating whether the repository has staged, but uncommitted changes

`tuulgit.check_status.has_unstaged_changes()`

Return a boolean indicating whether the working tree has unstaged changes

`tuulgit.check_status.has_untracked_unignored_files()`

Return a boolean indicating whether the working tree has untracked, unignored files

`tuulgit.check_status.is_clean_working_tree(check_if_working_tree=True)`

Return a boolean indicating whether the Git working tree is clean or not

`tuulgit.check_status.is_working_tree()`

Check if this is a git working tree at all

Raises `Tuulerror` – when the caller attempts to use this function outside of a git working tree

`tuulgit.check_status.repo_toplevel_path()`

Return a string containing the path of the repo's top-level directory

Git tag the commit on the current branch, *only if* the working tree is clean

`tuulgit.tag_commit.tag_current(tag)`

Git tag (annotated) the current commit from a clean working tree

Raises `Tuulerror` – when the caller attempts to tag an unclean working tree or to use a tag that already exists on the repo

`tuulgit.tag_commit.tag_current_signed(tag)`

Git tag (signed) the current commit from a clean working tree

Raises `Tuulerror` – when the caller attempts to tag an unclean working tree or to use a tag that already exists on the repo

`tuulgit.tag_commit.tag_delete_local(tag)`

Delete the named Git tag (local only). This function does *not* delete remote tags

Raises `Tuulerror` – if the tag delete fails

2.5 tuulver

Parsing tuuls for a tuulbachs-formatted version YAML input file.

Utility functions for managing a tuulbachs-formatted version YAML file

`tuulver.version.bump_build(filename)`

Bump the “build” portion of the version from the input YAML filename

`tuulver.version.bump_major(filename)`

Bump the major portion of the version from the input YAML filename

`tuulver.version.bump_minor(filename)`

Bump the minor portion of the version from the input YAML filename

`tuulver.version.bump_patch(filename)`

Bump the patch portion of the version from the input YAML filename

```
tuulver.version.bump_pre(filename, prebase='pre')
    Bump the "pre" portion of the version from the input YAML filename
tuulver.version.create_version_file(filename, product_name)
    Create an initial tuulbachs-formatted version YAML file
tuulver.version.emit_product_name(filename)
    Return the product name value from the input YAML filename
tuulver.version.emit_version(filename)
    Return the version value from the input YAML filename
```

2.6 tuulyaml

Low level tuools for interacting with YAML files.

Parse an input YAML file

```
tuulyaml.parse.parse_yaml(filename)
    Given input path filename, parse YAML file.
```

Update a simple top-level value in a YAML file

```
tuulyaml.update_simple_value.update_value(inout_path, existing_key, new_value)
    Update existing_key to new_value in the existing inout_path YAML file.
```

2.7 install

Note that tuulbachs is not yet published at PyPi.

1. Set up and activate a Python [virtual environment](#) at the top level of this project
2. `python -m pip install -r requirements.txt`
3. `cd` to the local `auto` directory
4. `./install_local.sh`

2.8 deploy

How to deploy updates to tuulbachs itself.

Prerequisite: User must have already followed [install](#) guidance at least once in the target environment.

1. Decide which type of [semantic version](#) upgrade this is (major, minor, patch, etc.)
2. From `tuulver/version.py`, use the appropriate `bump_*` function to update the version string in `version.yaml`
3. Follow [install](#) guidance
4. Commit changes to Git
5. From `tuuldevops/tag_current_version.py`, use the `tag_product_version` function to properly tag this release
6. Push the Git update (including tags) to this repo's remotes

7. In a temp dir, `download all required packages` without installing them, tar and zip these for deployment.
8. In the src dir, run `pyinstaller --add-data ../version.yaml:.. --onefile tuul.py`
9. Publish the release (including offline packages tarball and `tuul` executable) on the repo's remote (Github, for instance)

2.9 internal API

This is code intended for use by tuulbachs itself, not external users.

Project exception class

```
exception tuulbachs.exception.TuulError (msg=None)
    Class used for exceptions thrown by tuulbachs
```

2.10 Indices and tables

- genindex
- modindex

PYTHON MODULE INDEX

t

tuulbachs.exception, 8
tuulcli.cli_color, 5
tuuldevops.pipeline_steps, 5
tuuldevops.tag_current_version, 5
tuuldevops.update_version, 5
tuulgit.check_status, 6
tuulgit.tag_commit, 6
tuulver.version, 6
tuulyaml.parse, 7
tuulyaml.update_simple_value, 7

INDEX

B

bump_build() (*in module tuulver.version*), 6
bump_major() (*in module tuulver.version*), 6
bump_minor() (*in module tuulver.version*), 6
bump_patch() (*in module tuulver.version*), 6
bump_pre() (*in module tuulver.version*), 7

C

CliColor (*class in tuulcli.cli_color*), 5
create_version_file() (*in module tuulver.version*), 7

E

emit_product_name() (*in module tuulver.version*), 7
emit_version() (*in module tuulver.version*), 7

H

has_staged_uncommitted() (*in module tuulgit.check_status*), 6
has_unstaged_changes() (*in module tuulgit.check_status*), 6
has_untracked_unignored_files() (*in module tuulgit.check_status*), 6

I

is_clean_working_tree() (*in module tuulgit.check_status*), 6
is_working_tree() (*in module tuulgit.check_status*), 6

M

major_step() (*in module tuuldevops.pipeline_steps*), 5
module
 tuulbachs.exception, 8
 tuulcli.cli_color, 5
 tuuldevops.pipeline_steps, 5
 tuuldevops.tag_current_version, 5
 tuuldevops.update_version, 5
 tuulgit.check_status, 6

tuulgit.tag_commit, 6
tuulver.version, 6
tuulyaml.parse, 7
tuulyaml.update_simple_value, 7

P

parse_yaml() (*in module tuulyaml.parse*), 7

R

repo_toplevel_path() (*in module tuulgit.check_status*), 6

T

tag_current() (*in module tuulgit.tag_commit*), 6
tag_current_signed() (*in module tuulgit.tag_commit*), 6
tag_delete_local() (*in module tuulgit.tag_commit*), 6
tag_product_version() (*in module tuuldevops.tag_current_version*), 5
tuulbachs.exception
 module, 8
tuulcli.cli_color
 module, 5
tuuldevops.pipeline_steps
 module, 5
tuuldevops.tag_current_version
 module, 5
tuuldevops.update_version
 module, 5
TuulError, 8
tuulgit.check_status
 module, 6
tuulgit.tag_commit
 module, 6
tuulver.version
 module, 6
tuulyaml.parse
 module, 7
tuulyaml.update_simple_value
 module, 7

U

update_product_version() (*in module tuulde-
vops.update_version*), [5](#)
update_value() (*in module tu-
ulyaml.update_simple_value*), [7](#)